



In2p3



SPL Collaboration Meeting

—
IN2P3

Patxi DUTHIL

December 11th 2008

Contents

- *IPNO-IN2P3 (CNRS): the organization*
- *A brief history: IN2P3's contribution to the LHC*
- *IN2P3s experience in superconducting LINAC*
- *IPNO-IN2P3's facilities: the SUPRATECH platform*
- *IN2P3 contribution to the SPL project*


IPNO-IN2P3 (CNRS): the organization

CNRS
(French) National Center for Scientific Research

In2p3
IN2P3
(French) National Institute of Nuclear Physics and Particles Physics
www.in2p3.fr

University of Paris-Sud 11 (Orsay)
UNIVERSITÉ PARIS-SUD 11

Division DA
Accélérateurs
~100 workers



(CNRS - February 1996 → September 2006)

○ Cryostat and Short Straight Section assembly




- Arc: 360 units for 61 alternatives
- Dipole Sections: 64 units pour 34 alternatives
- Magnet Sections: 50 units pour 41 alternatives
- 65.3 Man.Year

○ Design

- Modular design
- Integration and interfaces study
- 3D models
- Numerical calculation notes

○ Documentation

- Technical specifications
- Components drawings
- Assembly drawings



Agreement n°2 (CNRS - February 1996 → September 2006):

- Dipoles, Arc, DS et MS assembly tools
Design, Calculations and assembly procedure for:
 - Tests Arc prototype
 - Cryostating Dipole
 - Assembly standard section Arc
 - Assembly standard section DS
 - Assembly standard section MS
 - Assembly Arc QQS, DS, MS



- Industrial follow-up:
 - Prototype components in several industries
 - Until BDT bankruptcy: Preparation of « Requests for proposal » for the serie and follow-up of the serie at BDT and several industries
 - Dipole Vacuum vessel at FCM (Spain): 313 units
 - Bottom Tray at SIMIC (Italy): 846 units




Agreement n°3 (CNRS - February 1996 → September 2006):

- Thermometry of the LHC
 - Category B: $50\text{ K} < T < 300\text{ K}$ → platinum thermometers were chosen
 - Category A: $1.6\text{ K} < T < 300\text{ K}$
 - several types of sensors might be used,
 - each thermometer needed a dedicated calibration.
 - Program selection of category A sensors:
 - thermal cycling → long term stability,
 - magnetic field influence,
 - neutrinos flux tests within liquid helium → radiation resistance

Range	1.6 K - 2.2 K	2.2 K - 4 K	4 K - 6 K	6 K - 25 K	25 K - 50 K	50 K - 300 K
Exactitude	± 10 mK	± 20 mK	± 30 mK	± 1K	± 5 K	± 5 K

Agreement n°3 (CNRS - February 1996 → September 2006):

- Thermometry of the LHC



A calibration set-up was designed

- ± 7 mK for $T < 2.2$ K,
- ± 10 mK for $2.2 \text{ K} < T < 30$ K,
- ≤ 0.25 % for $T > 30$ K.

Quality program:




Industrial organization for mass production in respect with the ISO norms.

3 inserts are now available:

- 2 for sensors calibration in vacuum,
- 1 for sensors calibration in liquid He.


2500 thermometers per year

○ RF simulations




Electro Magnetic simulation: MAFIA, Microwave Studio, HFSS, SOPRANO
 Optimization of E_{pk}/E_{acc} and B_{pk}/E_{acc} ratios


○ Mechanical simulations



04.005.011 Calcul Cosmosec - Déplacements
 Unités: mm - Echelle des Informations: 1: 100




URES
 2.962e-001
 2.716e-001
 2.480e-001
 2.222e-001
 1.976e-001
 1.728e-001
 1.481e-001
 1.236e-001
 9.916e-002
 7.471e-002
 4.936e-002
 2.400e-002
 1.000e-002




SAMCEF, COSMOS DesignStar, CASTEM
 Stress, eigen modes, coupling strain / frequency variation, Lorentz forces


- Displacement of a superconducting plunger into the magnetic field




- Wall deformation
5 Cellules 700 MHz



Fast tuning system: use of piezo-electric actuators
Spoke 350 MHz **EURISOL**






Spiral2 


Prototype and series cryomodules

Test cryomodule for **EURISOL**

European Isotope Separation On-Line
Radioactive Ion Beam Facility



○ *Clean room*



- *85 m2 total surface and 45 m2 class 10*
- *Ultra-pure water production, high pressure rinsing capability*
- *Temperature and humidity level controlled*
- *Distribution of He et N₂ clean gas*
- *Vacuum test inside the clean room*

○ Assembly hall



- *RF amplifier : 700 MHz 80 kW CW*
 - *Thalès tube 704.4 MHz, I.O.T. technology, 80 kW CW*
 - *Elliptical cavity tests : Eurotrans, Eurisol*



- *RF amplifier : 350 MHz 20 kW CW*
 - *Spoke cavity test: Eurisol, Eurotrans*



- Chemistry facility (FNP) (nearly operational)
 - bath HF:HNO₃:H₃PO₄
 - on-line treatment of gas effluent
 - on-line treatment of liquid (low acid concentration) effluent



- Helium liquefier
 - Linde technology
 - Max. liquefying capacity 65 l/h (with nitrogen pre-cooling)



- Recovery helium gas network and compression system



○ Cryogenics facilities

- RF and cryogenic tests in vertical cryostat
- Dimensions $\varnothing=800$ mm, H=2500 mm
- 2 K, 4 K without He tank, 4K with He tank
- Ampli.: 600 W @ 350 MHz and 1 kW @ 88 MHz
- RF driving (auto oscillant loop) 350 MHz, 88 MHz
- Thermometry
- Microphonics measurement by use of CRM
- Accelerometers set up (under progress)



○ Cryogenics facilities

- RF and cryogenic tests in cryomodules
 - Refrigeration facility: 60 kW @ 25°C
 - 2 amplis 10 kW solid state @ 88 MHz (Spiral 2)
 - 1 ampli 10 kW solid state @ 350 MHz (EURISOL)
 - 1 RF source: 80 kW (IOT) @ 700 MHz (EUROTRANS - under progress)





Spiral 2 cryomodule



CMO:
Horizontal cryomodule for tests

- *Future cryogenics facilities (under progress)*



- *Cooling system (400 kW thermal power)*
 - *Primary network (glycol): 7-12 °C*
 - *Secondary network (non ionized water): 15-25°C*



Capabilities of the Division Accelerators

- *RF cavities, beam dynamics, RF couplers, cryostats → from the design to the tests*
 - *Numerical simulation and optimization*
 - *Design, modeling, drawing*
 - *Industrial follow-up*
 - *Assembly*
 - *Tests in dedicated environment*
 - *Quality procedures*




- *Administrative and financial framework*
 - *Exceptional (additional) contribution of France to the CERN*
 - *1 collaboration protocol → CERN / CEA-CNRS*
 - *4 specific executive agreements (including specifications about each topic)*
 - *N°1 - LINAC 4*
 - *N°2 - SPL*
 - *N°3 - Superconductive magnets*
 - *N°4 - CLIC/CTF3*
 - *Work Packages descriptions*
 - *Work package templates have to be given*

- *WP3: Design and construction of a full-scale cryomodule prototype for the SPL*
- *The goals:*
 - *Demonstrate on a full-scale machine the construction capability of a cryomodule housing $\beta=1$ cavities and SC quadruples;*
 - *Validate and eventually lead to the improvement of the design and construction features;*
 - *Enable RF Testing on a multi-cavity assembly in a horizontal cryo-module driven by a single RF source;*
 - *Validate by testing critical components like RF couplers, and fast piezo tuners in their real operating environment;*
 - *Understand the mechanical behavior of the cryomodule at cryogenic temperature, in particular alignment issues and evaluate heat loads;*
 - *Learning of the critical assembly phases;*
 - *Estimate cryomodule construction costs*

- *CNRS-IN2P3 Tasks:*
 - 1/ *To design and integrate the cryostat and to provide cryostat components for one cryomodule prototype;*
 - 2/ *To design and provide the supporting/guiding system for the string of cavities in the cryostat;*

- *The deliverables:*
 - *Hardware components*
 - *Design and calculation reports, drawing files and design models (CATIA V5 R16);*
 - *Fully documented industrial production files:*
 - *Material spec.*
 - *Designed calculations (construction codes)*
 - *Production drawings*
 - *Assembly procedures*
 - *Quality assurance and safety records*

○ Cryomodule configuration



○ *Cryomodule dimensional specifications (to be fixed)*

	Value	Comment
Active elements		
Number of cavities	8	
Approx. length of a cavity in its helium vessel	1000 mm	between flanges
Approx. outer diameter of cavity helium vessel envelope	400 mm	following design under Task 3
Number of quadrupoles	2 (1 doublet)	
Length of quadrupole doublet	1.5 m (TBC)	Doublet design by CERN
Cryostat elements		
Approx. outer diameter of doublet helium vessel envelope	TBD	Doublet design by CERN
Approx. length of vacuum vessel	13.6 m (TBC)	Depends on cryostat design
Approx. outer diameter of vacuum vessel	1014 mm (36")	Depends on cryostat design
Approx. value of vacuum vessel thickness	12 mm	Depends on cryostat design
Approx. inner diameter of He Gas Return Pipe	300 mm (TBC)	Defined by mass flow/pressure drop
Approx. thickness of He Gas Return Pipe	6 mm (TBC)	Depends on cryostat design (CNRS) and GRP design (CERN)
Number of cold supports posts	3 (TBC)	Depends on cryostat design. LHC solution/technology can be applied.
Number of Thermal shields	1	Aluminium, active cooling 50-75 K
Thermal shield MLI protection	30 layers	According to LHC technology

○ *Positioning accuracy and stability of active elements*

Active element	Positioning accuracy of a string w.r.t. a reference beam axis					Positioning uncertainty/stability w.r.t. vacuum vessel fiducials (rms)			
	Transversal [mm]	Longitudinal [mm]	rot. x [deg.]	rot. y [deg.]	rot. z [deg.]	Transversal [mm]	rot. x [deg.]	rot. y [deg.]	rot. z [deg.]
Quadrupole	± 0.5	± 2	± 0.25	± 0.25	± 0.5	± 0.3	± 0.15	± 0.3	± 0.3
Cavity	± 0.5	± 2	± 0.08	± 0.08	N.A.	± 0.3	± 0.05	± 0.05	N.A.

x=radial; y=vertical; z=longitudinal

○ *Static heat loads per unit length (to be further defined)*

Heat Load @ 2 K [W/m]	Heat Load @ 5-10 K [W/m]	Heat Load @ 50-75 K [W/m]
0.15	1.5	5


○ Human resources and material costs

N°	TASK	INSTITUTE	MATERIAL COSTS (k€)	MANPOWER (man.months)
1	Cryostat design, integration and supplying of cryostat components for 1 cryomodule prototype	CNRS	124	42
2	Design and supplying of the supporting/guiding system for the string of cavities within the cryostat	CNRS	31	12
TOTAL		CNRS	155	54
TOTAL 2		CNRS+CEA	267	82.8

○ The team

- *Patxi DUTHIL*
Project organization, supervision, mechanical and thermal calculation
- *Sébastien BLIVET*
Design, CAD models, mechanical calculation, production drawings
- *Hervé SAUGNAC*
Mechanical and thermal calculation
- *François LAUNAY*
Numerical thermal calculation
- *Giles BELOT*
Industrial follow-up
- *Virginie LAURENCIER*
Financial aspects
- *Advisors for the design, the cryogenics and instrumentation aspects (SPIRAL 2, LHC, EUROTRANS, EURISOL)*

○ *Schedule*



Conclusion

- *Signature of the collaboration agreement is not yet finalized*
- *IN2P3 is ready to participate in the project*
 - *The project team is defined*
 - *The working framework (tools, software...) is operational*
- *But:*
 - *Need of a Product (Work) Breakdown Structure*
 - *Several specifications are to be defined*
 - *Project organization must be setup*

A lot of work for those two days...

THANK YOU !
